

RoHS


Reversion	Discription	Date	Signed
V0	First	2026-08-08	Penglz

NO.	SYMBOL
1	LEDK
2	LEDA
3	GND
4	TP_RST
5	TP_INT
6	TP_SCL
7	TP_SDA
8	TP VDD-3.3V
9	GND
10	VDDA
11	VDDI
12	TE
13	RST
14	CS
15	SCL
16	D0
17	D1
18	D2
19	D3
20	GND

QSPI

1	TP_RST
2	TP_INT
3	TP_SCL
4	TP_SDA
5	TP VDD-3.3V
6	GND

IIC 通信电压3.3V



If=80mA, Vf=3.0V (TYP)

FPC展开出货

NOTES:

- DISPLAY TYPE:2.23" TFT, TRANSMISSIVE
- DRIVER IC:Q936 or COMPATIBLE
- VIEWING DIRECTION: ALL
- BACKLIGHT: 4 pcs White LED
- BRIGHTNESS: 300cd/m2(TYP)
BRIGHTNESS: CTP+LCM -cd/m2(TYP)
- INPUT VOLTAGE : VCC 2.8V(TYP)
- OPERATING TEMP: -20° C~ +70° C
- STORAGE TEMP: -30° C~ +80° C
- UNDEFINED DIMENSION TOLERANCE: $\pm 0.3\text{mm}$
- RoHS COMPLYABLY
- 建议机壳开窗可视区比 LCD A. A区单边大 0.3mm

		深圳市华之洋光电科技有限公司					
		SHENZHEN HZY PHOTOELECTRIC TECHNOLOGY CO., LTD					
Customer Ref.	Model No.	Drawing Title		HZ0223WQPIS01-A0			

Part No.	Approve	Material	Unmarked Tolerance	Unit	Scale	Page	
---		LCM	± 0.2	mm	--	1 of 1	
Drawing No.	Draw	FJB	Date	2026-07-09	Rev V0	